

## GENERAL POWER LTD. INC.

8235 N.W. 64th St #2

Miami FL 33166 USA

Ph. 305-471-9566 Fax 305-471-9568

e-mail: info@genpowerusa.com

website: www.genpowerusa.com



### KGE2000Ti

#### Features and Benefits

- \*Maximum 2.00 kVA output for wide range of applications
- \*Low noise design, about 56-61dB/7m
- \*Lightweight delivers super portability only 22kg (49 lbs)
- \*4 hours running on a single fuel tank
- \*Inverter technology delivers quality output
- \*Stylish and patented design
- \*Unique and patented air cycle system
- \*Dual voltage and frequency output for ease of use

<b>Model</b>	KGE2000Ti
Rated Frequency (Hz)	60
Rated Voltage (V)	120/240
Rated current (A)	13.3/6.7
Rated speed (r/min)	5500
Rated Output (kVA)	1,6
Max Output (kVA)	2.0
<b>DC Output</b>	
DC Voltage	12V-8.3A
Electric Circuit Breaker	Available
Phase number	Single Phase
<b>Engine</b>	
Model	KG105
Type	Single Cylinder, 4 stroke, vertical, air cooled, OHV, Gasoline
Displacement (cc)	98,8
Rated Power HP/rpm	2.99/5500
Rated rotation speed (rpm)	5500
Ignition System	T.C.I.
Spark Plug	A7RTC
Starting System	Recoil Starter
Fuel	Automotive unleaded gasoline
Lube Oil	SAE10W30
<b>Miscellaneous</b>	
Fuel Tank Capacity (L)	2,5
Continuous running time (hr)(rated output)	4
Noise Level (zero load-full load)dB(A) 7m	56-61
Overall dimension (LxWxH) (mm)	513x296x426
Dry Weight kg (lbs)	22 (48.4)