



<b>PORTABLE POWER</b> GenSet
<b>DX4500</b>
Range <b>DIESEL</b>

longlife' engine  
low consumption  
Economy  
Circuit breaker  
Solid and compact frame

Diesel oil genset with electrical start for professional use - Low fuel consumption and high run time

General specifications	
Fréquency	60
Max power W	4000

Alternator specifications	
Type	MECC-ALTE S16W105
Régulation	Without ring nor brush
Protection class	IP 23
Insulation class	Class H

Engine specifications	
Brand	Yanmar
Type	L 70
Distribution	O.H.V.
Starting	Hand start
Fuel	Diesel Oil
Run time [h]	10.9
Fuel consumption [l/h]	1.1
Tank [l]	12
Oil guard	N
Cubic capacity [cm <sup>3</sup> ]	296
Oil capacity [l]	1.1

Sockets and panel	
1 x duplex 120V 15A (L5-15R) - circuit breaker + 1 x 120/240V 30A (L14-30R) - circuit breaker	

Dimensions and weight	
L x l x h dimensions [cm]	87 x 57 x 56
Weight [kgs]	72

Packaging	
Packaging	Carton/pallet
Dim Unitaire(Cm)	88x58,5x70
Cartons by Pal 120/80	4
Cartons by Pal 140/110	NA
Height Of Pallet (cm)	147



## Options



Trolley kit R07

R07 : For gensets > 3 kW : its new system with 4 handling bars avoids handling problems - Wheels diameter 300 mm



Earth spike RPQ

RPQ : Earth spike to earth your generating set. A 1 meter long galvanized spike delivered with a 2 meters long and 10 mm<sup>2</sup> gauge cable.



Cans of oil RBH0,5  
RBH1

RBH1/RBH0,5 : Box of 20 1L or 0,5 L cans of oil (SAE 15W40)



**GENERAL POWER LIMITED, INC**  
8235NW 64 Street #2  
Miami, Florida 33166  
P 305 471 9566 F 305 471 9568