



**PORTABLE POWER**  
GenSet  
**DX6500EC**  
Range **DIESEL**

longlife' engine  
low consumption  
Economy  
Electric start  
Solid and compact frame

Diesel oil genset with electrical start for professional use - Low fuel consumption and high run time

**LOW ENGINE OIL SAFETY**  
With this feature, not only does the engine start and stop with a simple turn of the key but, more importantly, it will not start (and will stop of its own accord if running) if the oil level is too low. Your generator set is fully protected!

General specifications	
Fréquency	60
Max power W	5500

Alternator specifications	
Type	MECC-ALTE MR1/180
Régulation	Without ring nor brush
Protection class	IP 23
Insulation class	Class H

Engine specifications	
Brand	Yanmar
Type	L100
Distribution	O.H.V.
Starting	Electrical start
Fuel	Diesel Oil
Run time [h]	7.1
Fuel consumption [l/h]	1.7
Tank [l]	12
Oil guard	Engine shut down on lack of oil pressure
Cubic capacity [cm3]	406
Oil capacity [l]	1.65

Sockets and panel
1 x duplex 120V 15A (L5-15R) - circuit breaker + 1 x 120V 30A (L5-30R) + 1 x 120/240V 30A (L14-30R) + hours counter

Dimensions and weight	
L x l x h dimensions [cm]	87 x 57 x 56
Weight [kgs]	105

Packaging	
Packaging	Carton/pallet
Dim Unitaire(Cm)	88x58,5x70
Cartons by Pal 120/80	4
Cartons by Pal 140/110	NA
Height Of Pallet (cm)	150



## Options



**Trolley kit R07**

R07 : For gensets > 3 kW : its new system with 4 handling bars avoids handling problems - Wheels diameter 300 mm



**Earth spike RPQ**

RPQ : Earth spike to earth your generating set. A 1 meter long galvanized spike delivered with a 2 meters long and 10 mm<sup>2</sup> gauge cable.



**Cans of oil RBH0,5  
RBH1**

RBH1/RBH0,5 : Box of 20 1L or 0,5 L cans of oil (SAE 15W40)



**GENERAL POWER LIMITED, INC**  
8235NW 64 Street #2  
Miami, Florida 33166  
P 305 471 9566 F 305 471 9568