



PORTABLE POWER
GenSet
ALIZE6500EC
Range **PRESTIGE**

Very silent
Large Autonomy
OHV Honda engine
electric start
Full control panel

Main use Ideal for work-site in urban areas and mobil trade (with sand filter)

General specifications	
Fréquency	60
Max power W	6000

Alternator specifications	
Type	MECC-ALTE MR1/180
Régulation	Without ring nor brush
Protection class	IP 23
Insulation class	Class H

Engine specifications	
Brand	Honda
Type	GX 390
Distribution	O.H.V.
Starting	Electrical start
Fuel	Unleaded Petrol (sans plomb)
Run time [h]	8.3
Fuel consumption [l/h]	2.9
Tank [l]	24
Oil guard	Engine shut down on low oil level
Cubic capacity [cm ³]	389
Oil capacity [l]	1.1

Sockets and panel
1 x duplex 120V 15A (L5-15R) - circuit breaker + 1 x 120V 30A (L5-30R) - circuit breaker + 1 x 120/240V 30A (L14-30R) - circuit breaker - hours counter

Dimensions and weight	
L x l x h dimensions [cm]	78 x 59 x 75
Weight [kgs]	130

Packaging	
Packaging	Carton+ Shrink
Dim Unitaire(Cm)	80x61x78,5
Cartons by Pal 120/80	4
Cartons by Pal 140/110	NA
Height Of Pallet (cm)	164



Options



Earth spike RPQ

RPQ : Earth spike to earth your generating set. A 1 meter long galvanized spike delivered with a 2 meters long and 10 mm² gauge cable.



Cans of oil RBH0,5
RBH1

RBH1/RBH0,5 : Box of 20 1L or 0,5 L cans of oil (SAE 15W40)



GENERAL POWER LIMITED, INC
8235NW 64 Street #2
Miami, Florida 33166
P 305 471 9566 F 305 471 9568