



**PORTABLE POWER**  
GenSet  
**ALIZE8000SDEC**  
Range **PRESTIGE**

Very Silent  
Very large autonomy  
longlife' engine  
electric start  
Full control panel

Main use Ideal for work-site in urban areas and mobil trade (with sand filter)

General specifications	
Fréquency	60
Max power W	7500

Alternator specifications	
Type	MECC-ALTE ECO3-2S
Régulation	With ring and brush
Protection class	IP 23
Insulation class	Class H

Engine specifications	
Brand	Mitsubishi
Type	L3E SD
Distribution	Water-cooling- 1800 tr/mn
Starting	Electrical start
Fuel	Diesel Oil
Run time [h]	15
Fuel consumption [l/h]	2.4
Tank [l]	36
Oil guard	Engine shut down on lack of oil pressure
Cubic capacity [cm3]	
Oil capacity [l]	3.6

Sockets and panel
1 x duplex 120V 15A (L5-15R) - circuit breaker + 1 x 120V 30A (L5-30R) - circuit breaker + 1 x 120/240V 30A (L14-30R) - circuit breaker - voltmeter - ammeter - emergency stop button - hours counter - selector support light - Lights test button - battery charging light - water temperature fault indicator - oil pressure fault indicator

Dimensions and weight	
L x l x h dimensions [cm]	144 x 66 x 83
Weight [kgs]	368

Packaging	
Packaging	Canopy + Shrink
Dim Unitaire(Cm)	144x66,5x83
Cartons by Pal 120/80	NA
Cartons by Pal 140/110	NA
Height Of Pallet (cm)	NA

## Options



### Road trailer R08A

R08A : Road trailer for ALIZE 7500 DE, ALIZE 6000 SDE, ALIZE 9015 TDE and ALIZE 12515 TDE (PTAC< 500 kgs without registration plate) - Total dimensions : 2,80 x 1,20 x 1,35 m - Net weight : 85 kgs



### Remote control R04

R04 : Separate panel with on/off switch, indicating light for "on" and generating failure - delivered without cable - ref R04



### Earth spike RPQ

RPQ : Earth spike to earth your generating set. A 1 meter long galvanized spike delivered with a 2 meters long and 10 mm<sup>2</sup> gauge cable.



### Cans of oil RBH0,5 RBH1

RBH1/RBH0,5 : Box of 20 1L or 0,5 L cans of oil (SAE 15W40)



**GENERAL POWER LIMITED, INC**  
**8235NW 64 Street #2**  
**Miami, Florida 33166**  
**P 305 471 9566 F 305 471 9568**