

# DSE8711/16

## STANDARD REMOTE DISPLAYS

### FEATURES



DSE8711



DSE8716



### KEY FEATURES

- 4-Line back-lit LCD text display
- Five key menu navigation
- Multiple display languages
- RS232 & RS485 communications
- Audible alarm
- Front panel mounting
- Protected front panel configuration for connected host controller
- Remote monitoring of connected host controller
- Maximum distance of 1.2 km from host controller when using RS485
- Easy access diagnostic page
- LED and LCD alarm indication
- Power monitoring (kW h, kV Ar, kV A h, kV Ar h)
- Additional display screens to help with modem diagnostics

### KEY BENEFITS

- 132 x 64 pixel ratio display for clarity
- Range of display options makes the system highly versatile to suit different load share application demands
- Data communication link allows remote system management
- IP65 rating (with supplied gasket) offers increased resistance to water ingress

### SUPPORTED MODULES WITH DSE8711

- DSE8610
- DSE8710

### SUPPORTED MODULES WITH DSE8716

- DSE8660
- DSE8760

### SPECIFICATION

#### DC SUPPLY

**CONTINUOUS VOLTAGE RATING**  
8 V to 35 V continuous

#### CRANKING DROPOUTS

Able to survive 0 V for 50 mS, providing supply was at least 10 V before dropout and supply recovers to 5 V. This is achieved without the need for internal batteries

#### MAXIMUM OPERATING CURRENT

140 mA at 12 V, 70 mA at 24 V

#### OUTPUTS

**ALARM OUTPUTS C & D**  
2 A DC at supply voltage

#### DIMENSIONS

**OVERALL**  
240 mm x 181 mm x 42 mm  
9.4" x 7.1" x 1.6"

#### PANEL CUTOUT

220 mm x 160 mm  
8.7" x 6.3"

#### STORAGE TEMPERATURE RANGE

-40 °C to +85 °C  
-40 °F to +185 °F

#### OPERATING TEMPERATURE RANGE

-30 °C to +70 °C  
-22 °F to +158 °F

### RELATED MATERIALS

#### TITLE

DSE871x Standard Remote Display Manual  
DSE871x Installation Instructions  
DSE8610 Data Sheet  
DSE8660 Data Sheet  
DSE8710 Data Sheet  
DSE8760 Data Sheet

#### PART NO'S

057-129  
053-071  
055-083  
055-086  
055-184  
055-185

### DEEP SEA ELECTRONICS PLC UK

Highfield House, Hunmanby Industrial Estate, Hunmanby YO14 0PH  
**TELEPHONE** +44 (0) 1723 890099 **FACSIMILE** +44 (0) 1723 893303  
**EMAIL** sales@deepseapl.com **WEBSITE** www.deepseapl.com

### DEEP SEA ELECTRONICS INC USA

3230 Williams Avenue, Rockford, IL 61101-2668 USA  
**TELEPHONE** +1 (815) 316 8706 **FACSIMILE** +1 (815) 316 8708  
**EMAIL** sales@deepseausa.com **WEBSITE** www.deepseausa.com

# DSE8711/16

## STANDARD REMOTE DISPLAYS

### FEATURES



The DSE8711/16 standard remote display modules are designed to provide superior remote display capabilities when used with the high-performance DSE86xx and DSE87xx synchronising & loadsharing control modules.

The display demonstrates exceptional data communication capabilities up to a maximum distance of 1.2 km from the Host DSEgenset controller.

This particular display has a 4-line text display, to provide the user with a clear and practical functional and operational understanding of all genset parameters in a multitude of different languages.

### ENVIRONMENTAL TESTING STANDARDS

#### ELECTRO MAGNETIC COMPATIBILITY

BS EN 61000-6-2  
EMC Generic Immunity Standard for the Industrial Environment  
BS EN 61000-6-4  
EMC Generic Emission Standard for the Industrial Environment

#### ELECTRICAL SAFETY

BS EN 60950  
Safety of Information Technology Equipment, including Electrical Business Equipment

#### TEMPERATURE

BS EN 60068-2-1  
Ab/Ae Cold Test -30 °C  
BS EN 60068-2-2  
Bb/Be Dry Heat +70 °C

#### VIBRATION

BS EN 60068-2-6  
Ten sweeps in each of three major axes  
5 Hz to 8 Hz at +/-7.5 mm, 8 Hz to 500 Hz at 2 gn

#### HUMIDITY

BS EN 60068-2-30  
Db Damp Heat Cyclic 20/55 °C at 95% RH  
48 Hours  
BS EN 60068-2-78  
Cab Damp Heat Static 40 °C at 93% RH  
48 Hours

#### SHOCK

BS EN 60068-2-27  
Three shocks in each of three major axes  
15 gn in 11 ms

#### DEGREES OF PROTECTION PROVIDED BY ENCLOSURES

BS EN 60529 IP65 - Front of module when installed into the control panel with the optional sealing gasket.

## COMPREHENSIVE FEATURE LIST TO SUIT A WIDE VARIETY OF LOAD SHARE APPLICATIONS

