

PI144K
Winding 06

STAMFORD

60Hz

RATINGS

Class - Temp Rise	Cont. F - 105/40°C 0.8pf			Cont. H - 125/40°C 0.8pf			Standby - 150/40°C 0.8pf			Standby - 163/27°C 0.8pf		
Series (V)	220	230	240	220	230	240	220	230	240	220	230	240
Parallel (V)	110	115	120	110	115	120	110	115	120	110	115	120
kVA	31.0	32.3	33.8	33.0	34.0	35.0	35.2	36.8	38.3	36.7	38.2	39.8
kW	24.8	25.8	27.0	26.4	27.2	28.0	28.2	29.4	30.6	29.4	30.6	31.8
Efficiency (%)	83.4	83.4	83.4	83.3	83.4	83.4	83.3	83.3	83.3	83.2	83.2	83.3
kW Input	29.7	31.0	32.4	31.7	32.6	33.6	33.9	35.3	36.7	35.3	36.8	38.2

Class - Temp Rise	Cont. F - 105/40°C 1.0pf			Cont. H - 125/40°C 1.0pf			Standby - 150/40°C 1.0pf			Standby - 163/27°C 1.0pf		
Series (V)	220	230	240	220	230	240	220	230	240	220	230	240
Parallel (V)	110	115	120	110	115	120	110	115	120	110	115	120
kVA	38.2	38.2	38.2	42.0	42.0	42.0	45.2	45.2	45.2	46.2	46.2	46.2
kW	38.2	38.2	38.2	42.0	42.0	42.0	45.2	45.2	45.2	46.2	46.2	46.2
Efficiency (%)	86.9	87.0	87.1	86.6	86.8	87.0	86.4	86.7	86.8	86.3	86.6	86.8
kW Input	44.0	43.9	43.9	48.5	48.4	48.3	52.3	52.1	52.1	53.5	53.3	53.2

DIMENSIONS

