



# M128

## Soundproofing canopy

### STANDARD FEATURES

- ➔ They protect stationary and mobile generator against the bad weather, against the theft and enables the reduction of the noise level.
- ➔ Enclosures are of 12 gauge steel. Steel sheet are electro zinc coated before painting (inside and outside) with a polyester powder rust inhibiting coat .
- ➔ High corrosion resistance: stainless covered with zinc and made in dichromate, bolts and rivets, anodized aluminium alloy hinges flexible seals between body sections.
- ➔ Soundfoam between 20 and 50 mm (1 to 2 in) acoustical sound treatment
- ➔ Lifting eye(s) on top of the enclosure fixed to the skid
- ➔ Large doors allow easy access to the generator set for service and monitoring purposes
- ➔ Window in "securit" glass mounted on enclosure door for control viewing .
- ➔ A residential silencer is mounted inside the enclosure
- ➔ Emergency stop button is accessible from outside enclosure.



Model	Sound level			Dimensions (mm)	Weight (kgs)	Tank (l)
	dB(A)@1m	dB(A)@7m	LWA			
	76	66		2300 x 1060 x 1680	1430	180

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. \*ISO 8528.

SDMO Industries – 12bis rue de la Villeneuve – CS 92848 – 29 228 BREST CEDEX 2  
Tel +33 (0)2 98 41 41 41 – Fax : +33 (0)2 98 41 63 07 – [www.sdmo.com](http://www.sdmo.com)