



## Container

### STANDARD FEATURES

- ➔ They protect stationary and mobile generator from rain and snow
- ➔ Paint: 1 coat anti-rust zinc primer ; 1 coat polyurethane primer ; 1 coat polyurethane finish (RAL9010 or according to RAL list)
- ➔ One high performance silencer installed on the container's roof
- ➔ Large doors allow easy access to the generator set for service. A door on the side of the side of the unit allow access for monitoring.
- ➔ Air-intake rain shield protection louvre as standard.
- ➔ Emergency stop button is accessible from outside enclosure.
- ➔ White paint finishing (RAL 9010)



| Model | Sound level |          |     | Dimensions<br>(mm)  | Weight<br>(kgs) | Tank<br>(l) |
|-------|-------------|----------|-----|---------------------|-----------------|-------------|
|       | dB(A)@1m    | dB(A)@7m | LWA |                     |                 |             |
|       | 91          | 81       |     | 12192 x 2438 x 2896 | 24600           | 500         |

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. \*ISO 8528.

SDMO Industries – 12bis rue de la Villeneuve – CS 92848 – 29 228 BREST CEDEX 2  
Tel +33 (0)2 98 41 41 41 – Fax : +33 (0)2 98 41 63 07 – [www.sdmo.com](http://www.sdmo.com)