



Weatherproof / Super Silent Enclosure

STANDARD FEATURES

- 12 gauge electro-zinc powder coated steel for maximum corrosion resistance (Phosphatizing degreasing, Non-chromic passivation, Osmosis purified rinsing and High durability polyester resin thermosetting powder paint)
- 29dB(A) Internal-mounted critical silencer and flexible exhaust connector offering maximum component life and operator safety
- Fade-, scratch-, and corrosion-resistant. Automotive-grade textured finish resulting in advanced corrosion and abrasion protection as well as enhanced edge coverage and color retention
- Up to 51mm (2in) Acoustic insulation with hydrocarbon sealing film that meets FMVSS 302 flammability classification and repels moisture absorption
- Interchangeable modular panel construction. Allows complete serviceability or replacement without compromising enclosure design
- Service access. Multi-personnel doors for easy access to generator set controller, breaker and service points
- Externally mounted emergency stop button, Single point lifting hook and Tamper proof "securit" viewing control window
- Cooling air discharge. Weather protective design featuring a vertical air discharge outlet grille. Redirects cooling air up and above enclosure to reduce ambient noise
- Cooling/combustion air intake with a horizontal air inlet. Sized for maximum cooling airflow
- Heavy duty Polyamide plastic hinges, Dichromate galvanized bolting and Stainless steel rivets for lifetime longevity
- Meets and exceeds NFX41002 Salt spray test, NFT30049 UV Performance test, NFT30038 Paint adhesion test and 2000/14EC Low sound directives



















RIGHT SIDE VIEW



LEFT SIDE VIEW







LEFT SIDE VIEW



LEFT SIDE VIEW







RIGHT SIDE VIEW



LEFT SIDE VIEW



